Luxury Vinyl Tile

Designer Outlet

GLUE DOWN

August 2026

GLUE DOWN — Gauge: 2.0mm ✦ Wear Layer: 0.2mm



4436 Nordic White Oak
184.2 x 1219.2mm



4432 Virginia Walnut
152.4 x 914.4mm



4501 Lava Stone
304.8 x 304.8mm



4503 Roman Marble
304.8 x 304.8mm



4526 Stencilled Concrete
304.8 x 304.8mm



4533 Glazed Metalstone
304.8 x 609.6mm



4531 Cottage Yorkstone
304.8 x 304.8mm

GLUE DOWN — Gauge: 2.0mm ✦ Wear Layer: 0.3mm



3806 Edwardian Oak
184.2 x 1219.2mm



3807 Coastal Limed Oak
184.2 x 1219.2mm



3508 Light Grey Cement
152.4 x 914.4mm



3489 Driftwood Light
152.4 x 1219.4mm



3494 Weathered Ash
184.2 x 1219.2mm



3499 Grey Beam
184.2 x 1219.2mm



3504 Washed Pine Dark
184.2 x 1219.2mm



9918 Botanic Oak
152.4 x 1219.2mm



9625 Malvern Oak
184.2 x 1219.2mm



2336 Classic Yorkstone
304.8 x 304.8mm

GLUE DOWN

Gauge: 2.0mm ✦ **Wear Layer:** 0.55mm



2050 Beige Limestone
304.8 x 609.6mm



2099 Light Metalstone
304.8 x 609.6mm



2102 Quarried Millstone
304.8 x 609.6mm



2105 Classic Concrete
304.8 x 609.6mm



2106 Black Slate
304.8 x 609.6mm



2155 Light Oak
184.2 x 1219.2mm

GLUE DOWN

Gauge: 2.5mm ✦ **Wear Layer:** 0.55mm



2836 Washed Pine Grey
184.2 x 1219.2mm



2838 Washed Pine Charcoal
184.2 x 1219.2mm



2841 Grey Stained Pine
184.2 x 1219.2mm



2912 Vintage Wood Beige
184.2 x 1219.2mm



2935 Grey Elm
152.4 x 1219.2mm



2946 Vintage Oak Grey
184.2 x 1219.2mm



1942 Driftwood Grey
152.4 x 914.4mm



4076 Brown Plywood
304.8 x 914.4mm



4075 Grey Plywood
304.8 x 914.4mm



PLK9563 Renaissance Oak
184.2 x 1219.2mm



SPQ9563
Renaissance Oak Small Parquet
76.2 x 228.6mm



LPQ9563
Renaissance Oak Large Parquet
101.6 x 609.6mm



SPQ9564
Berkley Oak Small Parquet
76.2 x 228.6mm



PLK9564 Berkley Oak
184.2 x 1219.2mm



9556 Base Cement
457.2 x 914.4mm



9557 Arista Terrazzo
457.2 x 914.4mm



2828 Weathered Concrete
457.2 x 914.4mm



2846 Original Concrete
457.2 x 914.4mm



2847 Industrial Concrete
457.2 x 914.4mm



2848 Vintage Metal
457.2 x 914.4mm



5059 Amazonian Slate
Size mix: 152.4 x 609.6mm /
304.8 x 3.408mm / 304.8 x 609.6mm



1997 Antique Travertine
457.2 x 457.2mm



1964 Pink Travertine
304.8 x 914.4mm



5048 Crème Swirl
457.2 x 457.2mm



5078 Nature Textile
609.6 x 609.6mm



1909 Terrazzo Special
457.2 x 457.2mm



2003 Limestone Putty
304.8 x 609.6mm



2980 Dovedale Stone
457.2 x 457.2mm



1982 Shellstone
457.2 x 457.2mm




1983 Limestone
457.2 x 457.2mm



1984 Sandstone
457.2 x 457.2mm

GLUE DOWN

Gauge: 3.0mm ✦ **Wear Layer:** 0.7mm



8076 Mocca Matrix
609.6 x 609.6mm



7107 Eggshell
457.2 x 457.2mm

Luxury Vinyl Tile

Designer Outlet

GLUE DOWN

August 2026

CHARACTERISTICS	STANDARD	2.0/0.2mm	2.0/0.3mm	2.0/0.55mm	2.5/0.55mm	3.0/0.7mm
Type of floor covering	ISO 10582 (EN 649)	Heterogeneous, PVC	Heterogeneous, PVC	Heterogeneous, PVC	Heterogeneous, PVC	Heterogeneous, PVC
Surface treatment		PUR	PUR	PU	PUR	PUR
Total weight	ISO 23997 (EN 430)	3680 g/m²	3600 g/m²	3520 g/m²	4290 g/m²	5100 g/m²
Performance classification	ISO 10874 (EN 685)	22	23, 31	23, 33, 42	23, 33, 42	23, 34, 43
Gauge	ISO 24346 (EN 428)	2.0mm	2.0mm	2.0mm	2.5mm	3.0mm
Wear layer thickness	ISO 24340 (EN 429)	0.2mm	0.3mm	0.55mm	0.55mm	0.7mm
Dimensional stability	ISO 23999 (EN 434)	≤0.10%*	≤0.10%*	≤0.25% max	≤0.10%*	≤0.10%*
Residual indentation	ISO 24343-1	<0.05mm*	<0.05mm*	≤0.1mm	<0.05mm*	<0.05mm*
Light fastness	ISO 105-B02 (Method 3)	≥6	≥6	≥6	≥6	≥6
Reaction to fire	EN 13501-1	Class Bfl-S1	Class Bfl-S1	-	Class Bfl-S1	Class Bfl-S1
Slip resistance**	DIN 51130 EN 13893	R10 Class DS	R10 Class DS	R10 Class DS	R10 Class DS	R10 Class DS
Static electrical propensity	EN 1815	≤2.0 kV classified as 'antistatic'	≤2.0 kV classified as 'antistatic'	-	≤2.0 kV classified as 'antistatic'	≤2.0 kV classified as 'antistatic'
Castor chair (continuous use)	ISO 4918 (EN 425)	Suitable	Suitable	-	Suitable	Suitable
Underfloor heating		Suitable, max. 27°C	Suitable, max. 27°C	-	Suitable, max. 27°C	Suitable, max. 27°C
VOC emissions	AgBB/ABG	Pass	Very low emissions	-	Very low emissions	Very low emissions
Plank Size		24 @ 152.4 x 914.4mm = 3.34m² 15 @ 184.2 x 1219.2mm = 3.37m²	24 @ 152.4 x 914.4mm = 3.34m² 18@ 152.4 x 1219.2mm = 3.34m² 15 @ 184.2 x 1219.2mm = 3.37m²	15 @ 184.2 x 1219.2mm = 3.37m² 18 @ 152 x 1219mm = 3.34m²	24 @ 152.4 x 914.4mm = 3.34m² 18 @ 152.4 x 1219.2mm = 3.34m² 15 @ 184.2 x 1219.2mm = 3.37m² 12 @ 304.8 x 914.4mm = 3.34m²	
Tile Size		18 @ 304.8 x 609.6mm = 3.34m² 36 @ 304.8 x 304.8mm = 3.34m²	36 @ 304.8 x 304.8mm = 3.34m²	18 @ 304.8 x 609.6mm = 3.34m²	18 @ 304.8 x 609.6mm = 3.34m² 8 @ 457.2 x 914.4mm = 3.34m² 16 @ 457.2 x 457.2mm = 3.34m² 9 @ 609.6 x 609.6mm = 3.34m² 12 @ 152.4 x 609.6mm 2 @ 304.8 x 304.8mm 6 @ 304.8 x 609.6mm = 3.34m²	16 @ 457.2 x 457.2mm = 3.34m² 9 @ 609.6 x 609.6mm = 3.34m²

* Average test value from current production.

** For clarification regarding slip, consult Polyflor technical services.

100% RECYCLABLE

Recofloor™ Vinyl Take-Back Scheme

UK CA BS EN 14041

CE EN 14041

POLYFLOR™ COVERING THE WORLD

UK Sales Direct: +44 (0)161 767 1122 | Export Sales Direct: +44 (0)161 767 1913
Sample Requests: +44 (0)161 767 2551 | Email: info@polyflor.com | **www.polyflor.com**