Altro Wood™ Comfort

safety flooring



1000 x 125mm

Reclaimed Oak | WSASC2821
WR335 / A1M335 / LRV 51



500/500 x 100mm

Soft Oak | WSASC2804
WR338 / A1M338 / LRV 38



Design as shown

Light Bamboo | WSASC2820
WR463 / A1M392 / LRV 42



500/500 x 100mm

Field Oak | WSASC2806
WR340 / A1M340 / LRV 37



550/450 x 100mm

Warm Maple | WSASC2805
WR339 / A1M339 / LRV 24



550/450 x 100mm

Deep Cherry | WSASC2803
WR337 / A1M337 / LRV 17



1000 x 125mm

Veteran Oak | WSASC2822
WR339 / A1M339 / LRV 22



550/450 x 100mm

Classic Walnut | WSASC2807
WR341 / A1M160 / LRV 15



500/500 x 100mm

Aged Oak | WSASC2815
WR347 / A1M347 / LRV 38



550/450 x 100mm

Antique Cherry | WSASC2802
WR336 / A1M239 / LRV 22



1000 x 125mm

Royal Oak | WSASC2823
WR322 / A1M239 / LRV 19



1000 x 166mm

Regent Oak | WSASC2825
WR468 / A1M62 / LRV 10

Dimensions indicate plank size within roll design.

10 year product guarantee

Pendulum test PTV ≥36

R10

1 in a million for life

14dB

altro EASYCLEAN™

low VOC

Altro Wood™ Comfort safety flooring Patent No. GB 2 462 167

5042 issue date 06/25

Typical applications

Entrances, corridors, communal areas. Bedrooms, quiet rooms, libraries. Wards. Classrooms.

Technical information

Fire behaviour tested in acc. with	EN ISO 9239-1	≥ 4.5 kW/m²
	EN ISO 11925-2	Pass
Classified in acc. with	EN 13501-1	C_{fl}-s1
Slip resistance	EN 13893	≥ 0.30 / DS
	EN 16165 Annex B / ASR A1.5	R10
		For enhanced safety, see our ranges that offer sustained slip resistance for life.
Sound insulation	EN ISO 10140	ca. 14 dB
Flooring type	EN 651	Heterogeneous floor
Thickness	EN ISO 24346	2.85 mm
Wear layer thickness	EN ISO 24340	0.7 mm
Roll dimensions	EN ISO 24341	2 m x 20 m = 40 m²
Weight	EN ISO 23997	2.6 kg/m²
Residual indentation	EN ISO 24343-1	≤ 0.20 mm
Classification for use	EN ISO 10874	34, 42
Flexibility	EN ISO 24344	Pass
Light fastness	EN ISO 105-B02	≥ 6
Castor chair abrasion	ISO 4918	Yes, type W
Wear resistance	EN 660-2	Group T
Chemical resistance	EN ISO 26987	Good
Underfloor heating	EN 12524	Suitable
Electrical behaviours	EN 1815	≤ 2 kV, antistatic
VOC emissions	CDPH 1350 / Floorscore	Approved
	Indoor Air Comfort Gold	Approved

Altro Limited a company certified by SGS to ISO 9001 and ISO 14001.

1658 EN 14041

0321 EN 14041

*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

Sustainability

†A+ BRE generic green guide rating for resilient flooring, full details available at **www.thegreenguide.org.uk**

Installation and maintenance

Please refer to Altro installation and maintenance instructions. Failure to follow these instructions can affect product performance and may affect or invalidate Altro's product guarantee. Technical information on installation and maintenance (including cleaning and staining) can be found at www.altro.com

Light Reflectance Values measured in accordance with BS 8493:2008. Exact material match with samples cannot be guaranteed.
Codes: WR = weld rod, A1M = mastic, LRV = light reflectance value

Altro, Designed for possibilities. Made for people. Altro Wood Comfort and Altro Easyclean Technology are trademarks of Altro Limited.

United Kingdom +44 (0) 1462 707 700 enquiries@altro.com
Australia +61 3 9764 5666 info@asf.com.au

Subject to alteration.