

# Altro Aquarius™

bathroom and wet room safety flooring




Cygnet | AQ2004
WR287 / A1M79 / LRV 46




Sea Snail | AQI2024
WR370 / A1M370 / LRV 50




Iguana | AQ2021
WR297 / A1M20 / LRV 41




Swan | AQI2012
WR291 / A1M01 / LRV 75




Puffin | AQI2005
WR287 / A1M79 / LRV 46




Dragonfly | AQ2001
WR292 / A1M292 / LRV 33




Vole | AQ2010
WR289 / A1M265 / LRV 43



Treefrog | AQI2003
WR293 / A1M271 / LRV 33



Walrus | AQ2007
WR261 / A1M81 / LRV 29



Blue Penguin | AQI2002
WR288 / A1M71 / LRV 24




Terrapin | AQI2009
WR289 / A1M265 / LRV 40



Gosling | AQI2023
WR369 / A1M369 / LRV 59




Tern | AQI2008
WR261 / A1M81 / LRV 31




Newt | AQ2022
WR368 / A1M368 / LRV 10




Otter | AQI2006
WR290 / A1M239 / LRV 26




Salamander | AQI2011
WR294 / A1M294 / LRV 41



Hippo | AQI2013
WR301 / A1M82 / LRV 11



Mallard | AQI2015
WR302 / A1M302 / LRV 13



Coral Crab | AQI2014
WR300 / A1M42 / LRV 14



Spoonbill | AQI2016
WR303 / A1M303 / LRV 11

10 year product guarantee

Pendulum test PTV ≥50

R11

1 in a million for life

altro EASYCLEAN™

low VOC

All shoes and barefoot

# Altro Aquarius™

Patent number GB 2 462 167 Patent number GB 2 496 644

5462 issue date 04/26

## Typical applications

Bathrooms. Showers. Changing rooms (except where spikes / studs – see our heavy duty ranges). Saunas. Spas. Wet rooms. Home adaptation level access bathrooms. Therapy pools with specialist care.

## Technical information

| | | | |
|---|---|---|---|
| | Fire behaviour tested in acc. with | EN ISO 9239-1<br>EN ISO 11925-2 | ≥ 8 kW/m²<br>Pass |
| | Classified in acc. with | EN 13501-1 | $B_{fl}$-s1 |
| | Slip resistance | EN 13893<br>PTV<br>EN 16165 Annex B / ASR A1.5<br>EN 13845 Annex C<br>EN 16165 Annex A | ≥ 0.30 / DS<br>≥ 50 (slider 96)<br>R11<br>ESf / ESb<br>B |
| | Sound insulation | EN ISO 140-8 | ca. 5 dB |
| | Flooring type | EN 13845 | Safety flooring |
| | Thickness | EN ISO 24346 | 2 mm |
| | Wear layer thickness | EN ISO 24340 | 2 mm |
| | Roll dimensions | EN ISO 24341 | 2 m x 20 m = 40 m² |
| | Weight | EN ISO 23997 | 2.6 kg/m² |
| | Residual indentation | EN ISO 24343-1 | ≤ 0.10 mm |
| | Classification for use | EN ISO 10874 | 34, 43 |
| | Flexibility | EN ISO 24344 | Pass |
| | Dimensional Stability | EN ISO 23999 | ≤ 0.4 % |
| | Light fastness | EN ISO 105-B02 | ≥ 6 |
| | Castor chair abrasion | EN 425 | Yes, type W |
| | Wear resistance | EN 13845 Annex D | ≤ 10% / 50000 cycles |
| | Chemical resistance | EN ISO 26987 | Good |
| | Underfloor heating | EN 12524 | Suitable |
| | Electrical behaviours | EN 1815 | ≤ 2 kV, antistatic |
| VOC | VOC emissions | CDPH 1350 / Floorscore | Approved |

CERTIFIED ISO 9001 ISO 14001

1029 EN 14041

0120 EN 14041

EMISSIONS DANS L'AIR INTÉRIEUR A+

*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

floor score

EMISSION CLASS FOR BUILDING MATERIALS M1

## Sustainability

BRE A+ Rated†

†A+ BRE generic green guide rating for resilient flooring, full details available at **www.thegreenguide.org.uk**

Phthalate-free

Contains bio-plasticiser

BRE Global Verified EPD

EN 15804 SD207

EPD No.: 000693

Contains recyclate

Recofloor™ Vinyl Take-Back Scheme

## Installation and maintenance

Please refer to Altro installation and maintenance instructions. Failure to follow these instructions can affect product performance and may affect or invalidate Altro's product guarantee. Technical information on installation and maintenance (including cleaning and staining) can be found at www.altro.com

Light Reflectance Values measured in accordance with BS 8493:2008. Exact material match with samples cannot be guaranteed.
Codes: WR = weld rod, A1M = mastic, LRV = light reflectance value

altro, Altro, Altro Aquarius and Altro Easyclean Technology are trademarks of Altro Limited.

**United Kingdom** +44 (0) 1462 707 700 enquiries@altro.com

**Australia** +61 3 9764 5666 info@asf.com.au

Subject to alteration.